

## SPECIFICATION

### TITLE OF THE INVENTION

OPTICAL RECORDING APPARATUS, OPTICAL RECORDING METHOD,  
PROGRAM AND MEDIUM

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The present invention relates to an optical disk apparatus that, for example, converges a luminous flux emitted from a light source on an information recording surface through a transparent substrate of an optical disk, and performs information recording and reproduction on the information recording surface.

#### Related Art of the Invention

Light converged on the information recording surface of an optical disk is converged into the smallest light spot when the phase is uniform. However, in actuality, aberrations exist in optical systems that condense a luminous flux emitted from a light source on the information recording surface of an optical disk. Because of this, the phase becomes nonuniform, so that the luminous flux is converged into a light spot slightly larger than a so-called diffraction-limited light spot formed when there is no aberration. Aberrations in optical systems that are permissible in an optical apparatus are generally known as the

Marechal criterion, and the value thereof is, when the wavelength of the light is  $\lambda$ , substantially  $0.07 \lambda$  in RMS (root-mean-square) value.

Since the intensity of a light spot exhibits a Gaussian distribution where the intensity is maximum at the center and rapidly decreases with distance from the center, the energy supplied to the recording film of the disk during recording is concentrated on the center of the spot.

At the same light source output, when the spot diameter increases due to aberrations in the optical system, the energy at the center of the spot is lower than that when there is no aberration, so that the energy supplied to the recording film is lower. This degrades recording characteristics.

The aberrations in optical systems include aberrations of optical parts, aberrations due to residual adjustment errors of optical systems, aberrations due to tilts of optical disks, base material thickness errors of optical disks and variations in refractive index and aberrations due to control errors such as defocus.

Of these aberrations, aberrations of optical parts and aberrations due to residual adjustment errors of optical systems are specific to apparatuses. Therefore, the light source outputs can be adjusted in advance by initial adjustment of optical disks. Of other energy decreasing factors, for the factors that do not vary with disk rotation (specifically,

factors dependent on the composition of the recording film of the optical disk), the light source output set value that yields the best recording quality can be obtained by so-called recording power learning to perform trial recording while changing the light source output in several steps.

This prior art is effective against the energy varying factors that do not vary with disk rotation and tries to provide a practicable optical disk apparatus without limiting the aberrations in optical systems to strict specifications that are difficult to realize.

However, when there is a factor that varies with disk rotation such as a local variation in disk tilt or a local variation in base material thickness and the energy density reduction cannot be compensated for by the recording power learning or a tilt control to tilt the entire optical system so that the optical axis is vertical to the disk, reduction in recording signal quality cannot be avoided.

Specifically, the light source wavelength has been decreasing and the density has been increasing with increasing NA (numerical aperture) particularly in recent years, and with this, spherical aberration due to a variation in disk base material thickness increases.

For example, when the wavelength and the NA are 650 nm and 0.6 which are used for DVDs, respectively, the spherical aberration caused by a base material thickness error of 10  $\mu$

m is only  $0.01 \lambda$ ; however, when the wavelength and the NA are 405 nm and 0.85, respectively, the spherical aberration is  $0.10 \lambda$  which exceeds the Marechal criterion and is as large as ten times the spherical aberration caused in the case of DVDs.

As is apparent from this, in the latter case, to suppress the spherical aberration to approximately  $0.03 \lambda$  that does not disturb recording and reproduction, a base material thickness error of only  $3 \mu\text{m}$  is permissible. However, a base material thickness variation of this extent can occur within one track of a disk. Particularly, on inner and outer tracks of a disk, the variation can be larger. In such a case, a recording energy variation that cannot be compensated for by the recording power learning occurs due to a variation in spherical aberration, so that deterioration of recording signal quality cannot be avoided.

For factors that vary moderately, for example, a warp of the disk due to a temperature increase in the optical disk apparatus, it is necessary to perform the recording power learning over again as required, and when image data continuing for a long time is recorded, learning cannot always be performed at an appropriate time. In a case where learning is performed when recording is started, there is a wait of the time necessary for the learning before recording is started, and this hinders the promptness of the operation of the apparatus.

As described above, for example, a recording energy variation that cannot be compensated for by the recording power

learning occurs, so that deterioration of recording signal quality cannot be avoided.

#### SUMMARY OF THE INVENTION

In view of the above-mentioned prior art problem, an object of the present invention is to provide an optical recording apparatus, an optical recording method, a medium and an information aggregate capable of suppressing the deterioration of recording signal quality that cannot be prevented by the conventional method.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215

SUB 3427 where  $S=0$  is  $P_0$ , the output is  $P_0/(1-K \cdot S^2)$  for a predetermined constant  $K$ .

SUB 3437 The 3rd invention of the present invention is an optical recording apparatus according to 1st invention, wherein said aberration amount is substantially a spherical aberration amount and/or a coma aberration amount.

SUB 3447 The 4th invention of the present invention is an optical recording apparatus according to 3rd invention, wherein said detection means is capable of detecting the spherical aberration amount and the coma aberration amount, and outputs the spherical aberration amount as a spherical aberration detection signal  $S_1$  and outputs the coma aberration amount as a coma aberration detection signal  $S_2$ , and wherein said control means controls the output of the light source so that, when the output of the light source necessary for the recording under a condition where  $S_1=S_2=0$  is  $P_0$ , the output is  $P_0/(1-K \cdot (S_1^2+S_2^2))$  for a predetermined constant  $K$ .

SUB 3457 The 5th invention of the present invention is an optical recording apparatus according to 3rd invention, wherein said information recording is performed on an optical disk, wherein said detection means detects and outputs a tilt amount of the optical disk as the signal associated with the aberration amount, and wherein the coma aberration amount is calculated based on a predetermined relationship that holds between the coma aberration amount and the tilt amount.

SUBA 7

The 6th invention of the present invention is an optical recording apparatus according to 2nd invention, wherein said information recording is stopped when  $1/(1-K \cdot S^2) > 1.5$ .

SUBA 7

The 7th invention of the present invention is an optical recording apparatus according to 1st invention, wherein said detection means detects the detected aberration amount as an aberration detection signal S, and wherein when the aberration detection signal and the output of the light source obtained by initial learning in the recording are  $S_i$  and  $P_i$ , respectively, said control means controls the output of the light source so that the output is  $P_i(1-K \cdot S_i^2)/(1-K \cdot S^2)$  for a predetermined constant K.

SUBA 8

The 8th invention of the present invention is an optical recording method of controlling a light source for generating a light spot used for information recording, said method comprising:

a detection step of detecting an aberration amount of the light spot or a signal associated with the aberration amount; and

a control step of controlling an output of the light source by use of the detected aberration amount or the associated signal.

SUBA 9

The 9th invention of the present invention is a program for causing a computer to function as all or part of the control means of the optical recording apparatus according to any one of 1st to 7th inventions.

SUB 107  
The 10th invention of the present invention is a program for causing a computer to perform all or part of the control step of the optical recording method according to 8th invention.

SUB 117  
The 11th invention of the present invention is a medium carrying a program for causing a computer to function as all or part of the control means of the optical recording apparatus according to any one of 1st to 7th inventions, said medium being computer-processable.

SUB 127  
The 12th invention of the present invention is a medium carrying a program for causing a computer to perform all or part of the control step of the optical recording method according to 8th invention, said medium being computer-processable.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an explanatory view of a necessary light source output when spherical aberration exists;

FIG. 2 is an explanatory view of a necessary light source output when coma aberration exists;

FIG. 3 is an explanatory view of a necessary light source output when both spherical aberration and coma aberration exist;

FIG. 4 is an explanatory view showing a relationship between a disk tilt and coma aberration; and

FIG. 5 shows the structure of an optical disk apparatus according to an embodiment of the present invention.

[Explanation of Reference Numerals]



- 1 Lens
- 2 Optical disk
- 3 Beam splitter
- 4 Light receiving element
- 5 Semiconductor laser
- 6 Detection means
- 7 Control means

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, an embodiment of the present invention will be described with reference to the drawings.

First, the structure and the operation of an optical disk apparatus of the present embodiment will be described with reference to FIG. 5 showing the structure of the optical disk apparatus of the present embodiment. An embodiment of the optical recording method of the present invention will be described at the same time when the operation of the optical disk apparatus of the present embodiment is described.

The optical disk apparatus of the present embodiment has a semiconductor laser 5 for generating a light spot on an optical disk 2, detection means 6 of detecting the aberration amount of the generated light spot, and control means 7 of controlling the output from the semiconductor laser 5 by use of the detected aberration amount. The optical disk apparatus of the present embodiment corresponds to the optical recording apparatus of

the present invention.

The light emitted from the semiconductor laser 5 passes through a beam splitter 3 and is condensed on the optical disk 2 by a lens 1. The light reflected from the optical disk 2 is condensed by the lens 1, reflected at the beam splitter 3, and condensed on a light receiving element 4.

Using the light condensed on the light receiving element 4, the detection means 6 detects the aberration amount of the light spot as a detection signal S for detecting the aberration amount. The control means 7 sets the light source output to a value calculated by an expression 7 shown later in accordance with the detection signal 7 as described below in detail.

Next, the principle of the present invention will be described in detail that deterioration of recording signal quality is prevented by adjusting the light source output based on an analysis of the variation in the energy contributing to recording which variation is caused due to an aberration variation.

Since the energy supplied to the recording film of the disk during recording is concentrated on the center of the light spot as mentioned above, the magnitude of the center intensity is substantially proportional to the energy contributing to recording.

Therefore, when the center intensity under an ideal condition where there is no aberration in the optical system

is  $I_0$  and the center intensity when aberrations exist is  $I$ , the ratio  $I/I_0$  therebetween is, as is apparent from the description given above, equivalent to the ratio of the energy contributing to recording when aberrations exist to the energy contributing to recording under the ideal condition.

Therefore, when aberrations exist, by making the light source output higher than an output  $P_0$  under the ideal condition at a ratio  $I_0/I$  which is the reciprocal of  $I/I_0$ , the energy contributing to recording can be maintained equal to that when there is no aberration. That is, this is achieved by setting the light source output to  $P$  calculated by the following expression 1:

[Expression 1]

$$P = (I_0/I) \cdot P_0$$

The center intensity ratio  $I/I_0$  is generally called Strehl ratio. When the RMS value of spherical aberration (hereinafter, referred simply to aberration) is  $W$ , the following expression 2 holds approximately:

[Expression 2]

$$I/I_0 = 1 - (2\pi W/\lambda)^2$$

Of the aberrations generated in optical disk apparatuses, except the components that can be measured in advance and do not vary with disk rotation, spherical aberration and coma aberration are predominant among aberrations that can vary during the operation, and causes therefor are local variations in the

base material thickness and the tilt of the disk as mentioned above.

For spherical aberration and coma aberration, various methods of detecting the aberration amount have been proposed. As described above, the optical disk apparatus of the present embodiment has such detecting means. The detection signal  $S$  which is proportional to the aberration amount  $W$  is expressed by the following expression 3 by use of a detection sensitivity  $C$  (constant):

[Expression 3]

$$S = C \cdot W$$

Here, the inventor of the present application has found that the following expression 4 holds by using the expressions 2 and 3:

[Expression 4]

$$I/I_0 = 1 - (2\pi S / (C\lambda))^2$$

That is, the expression 4 represents the relationship between the detection signal  $S$  which is the output of the detection means of detecting the aberration amount and the Strehl ratio  $I/I_0$ . The inventor of the present application has found that a desired light source output  $P$  is obtained through the Strehl ratio  $I/I_0$  by obtaining the detection signal  $S$  from the expressions 4 and 1.

Further, letting

[Expression 5]

$$K = (2\pi / (C\lambda))^2$$

to simplify the expression 4, since the terms on the right side of the expression 5 are all constants, K can be treated as one constant, so that the expression 4 can be expressed as the following expression 6:

[Expression 6]

$$I/I_0 = 1 - K \cdot S^2$$

Therefore, from the expressions 1 and 6, the following expression 7 is obtained:

[Expression 7]

$$P = P_0 / (1 - K \cdot S^2)$$

When the optimum light source output  $P_0$  under a condition where there is no base material thickness error or tilt variation is known, by setting the light source output to a value calculated by the expression 7 in accordance with the detection value  $S$  of the detecting means of detecting the aberration, the energy contributing to recording can be maintained substantially constant even when there is an aberration variation, so that deterioration of recording signal quality can be prevented.

This control method is based on a completely different idea from the conventional control methods by aberration correction such as the tilt control and the spherical aberration control. The conventional controls which are performed by physically moving a part or the whole of the optical system cannot sufficiently respond to high-speed variations as those caused

while the disk is rotating. However, the control of the present invention which is electrically performed can sufficiently respond to high-speed variations.

The value of the constant  $K$  which is obtained by substituting the sensitivity  $C$  of the aberration detection means into the expression 5 may directly be obtained by measuring the optimum light source output by causing a known base material thickness variation or tilt variation at the time of the initial adjustment of the optical disk apparatus.

FIG. 1 shows a comparison between an output ratio obtained, assuming that the aberration is spherical aberration, by calculating the Strehl ratio when spherical aberration exists by an FFT analysis and substituting the calculated Strehl ratio directly into the expression 1 and an output ratio obtained by substituting the aberration amount into the expression 7. For simplicity, it is assumed that the aberration detection sensitivity  $C$  is 1. FIG. 2 is a graph in the case of coma aberration obtained, assuming that the aberration is coma aberration, in a similar manner to the case of spherical aberration.

In any case, the result by the FFT analysis is substantially the same as the result by the expression 7 using the expression 2 which is an approximate expression. Therefore, it is apparent that the setting of the light source output by the expression 7 is effective.

The above described is a case where a single kind of

aberration exists, and the aberration signal is represented by the single symbol  $S$ . However, in actual optical disk apparatuses, spherical aberration and coma aberration can be generated at the same time. Even in such a case, in optical disk apparatuses having both detection means for spherical aberration and detection means for coma aberration, the operation expressions can be derived based on the same idea.

A wavefront aberration  $W$  which is the square root of the sum of squares of the aberration components is expressed as shown below when spherical aberration is  $W_1$  and coma aberration is  $W_2$ . In the description given below, the symbols associated with spherical aberration are marked with a numerical subscript 1, whereas the symbols associated with coma aberration are marked with a numerical subscript 2.

[Expression 8]

$$W^2 = W_1^2 + W_2^2$$

A relationship shown by the following expression 9 holds between the aberration  $W_1$  and an aberration detection signal  $S_1$  like the expression 3, and similarly, a relationship shown by the following expression 10 holds between the aberration  $W_2$  and an aberration detection signal  $S_2$ :

[Expression 9]

$$S_1 = C_1 \cdot W_1$$

[Expression 10]

$$S_2 = C_2 \cdot W_2$$

C1 and C2 are detection sensitivities of the aberrations. Since the detection means of detecting aberrations are normally provided with a volume for electrically controlling the sensitivity, the detection sensitivities of spherical aberration and coma aberration can be set to be substantially the same. For example, the detection signal voltage per an aberration of  $0.01 \lambda$  can be set to 10 mV. The detection sensitivity in this case is  $1.0 \text{ V}/\lambda$ . When the sensitivities set to be substantially the same as described above are C, the following expression is derived from the expressions 8 to 10:

[Expression 11]

$$W^2 = (S_1^2 + S_2^2) / C^2$$

Substituting the expression 11 into the expression 2 and reorganizing the expression 2, similarly,

[Expression 12]

$$I/I_0 = 1 - (2\pi / C\lambda)^2 (S_1^2 + S_2^2)$$

[Expression 13]

$$P = P_0 / (1 - K \cdot (S_1^2 + S_2^2))$$

FIG. 3 shows a comparison between an output ratio  $P/P_0$  obtained by calculating the Strehl ratio by the FFT analysis and substituting the calculated Strehl ratio directly into the expression 1 and an output ratio  $P/P_0$  obtained by substituting the aberration amount into the expression 13 for various combinations of spherical aberration and coma aberration. The horizontal axis of FIG. 3 represents a composite wavefront



aberration expressed by the square root of the sum of squares of spherical aberration and coma aberration. In this case, it is apparent that these output ratios are in good agreement with each other like in the case described with reference to FIGs. 1 and 2. As described above, by the expression 13, the light source output compensation value can accurately be obtained also when spherical aberration and coma aberration are generated at the same time.

While the method of detecting spherical aberration and coma aberration is not detailed in the description given above, any of the proposed various detection methods may be used. For example, an aberration detection signal is used that is obtained by a method such that the reflected light from the optical disk is divided into a plurality of regions by a hologram, the light beams are separately detected by the corresponding photodetectors and an aberration detection signal is generated from the signals thereof as shown in Japanese Patent Application Laid-open No. H12-155979. Optical disk apparatuses having a low margin for disk tilts frequently employ a tilt servo that directly detects the tilts of the optical axis and the disk surface and corrects the tilts. In such optical disk apparatuses, the method of detecting a disk tilt can be applied to the present invention as it is. FIG. 4 shows a relationship between the amount of a disk tilt and a calculation value of the amount of coma aberration generated in accordance with the disk tilt. Coma

aberration is substantially proportional to the disk tilt within a range of approximately the disk tilt  $\pm 1^\circ$  which is normally considered a problem in optical disk apparatuses. Therefore, the tilt detection signal can be used as the coma aberration detection signal as it is.

The signal associated with the aberration amount of the present invention corresponds to the tilt detection signal.

In the Marechal criterion generally regarded as a criterion for securing recording and reproduction quality, the RMS value of the wavefront aberration is  $0.07 \lambda$  as mentioned above. Substituting this into the expression 2,  $I/I_0=0.807$ , and the light source output set value in this case is  $P=1.24P_0$  from the expression 1. Therefore, when the light source output set value exceeds this value, even if recording is performed, recording of sufficient quality is not performed. Since in actual optical disk apparatuses, the light source output normally has a margin of approximately 20% to deal with variations in the sensitivity of the recording film of the disk, when this is considered, the light source output limit set value for securing recording quality is  $P=1.2 \times 1.24P_0=1.49P_0$ . Therefore, to secure sufficient recording quality, when the light source output set value calculated by the expression 7 satisfies

[Expression 14]

$$P/P_0 > 1.5,$$

defective recording is suppressed by performing a control so

that the recording sequence is stopped before recording is performed.

While in the present embodiment, the cases of spherical aberration and coma aberration which normally become a problem in the conventional optical disk apparatuses are described, since the approximate relational expression 2 of the Strehl ratio and the wavefront aberration holds irrespective of the kind of the aberration, it is obvious that when an aberration other than spherical aberration and coma aberration, for example, astigmatism or a third- or higher-order aberration is a problem, the aberration can be dealt with in a similar manner to the above-described cases as long as a detection method for the aberration is provided.

As is apparent from the description given above, the optical disk apparatus of the present invention is structured, for example, as follows: Means of detecting the aberration amount of a light spot is provided, and recording is performed at the light source output  $P$  calculated by  $P = P_0 / (1 - K \cdot S^2)$  where  $S$  is the aberration detection signal and  $P_0$  is the light source output necessary for recording when  $S$  is 0. Here,  $K$  is a constant.

Moreover, the aberration is mainly spherical aberration and/or coma aberration.

Moreover, means of detecting the coma aberration amount and the spherical aberration amount of a light spot is provided, the detection sensitivities of the aberrations are set to be

substantially the same, and recording is performed at the light source output  $P$  calculated by  $P = P_0 / (1 - K \cdot (S_1^2 + S_2^2))$  where  $S_1$  is the spherical aberration detection signal,  $S_2$  is the coma aberration detection signal and  $P_0$  is the light source output necessary for recording when  $S_1$  and  $S_2$  are both 0. Here,  $K$  is a constant.

Moreover, when the aberration is coma aberration, aberration detection is performed by disk tilt detection.

Moreover, when the light source output set value satisfies  $P/P_0 > 1.5$ , recording is stopped.

These realize an optical disk apparatus offering excellent performance by performing recording energy compensation not requiring learning by calculating by use of the aberration detection signal the light source output compensation amount necessary for compensating for the decrease in recording power due to spherical aberration and/or coma aberration being main aberrations that vary while the optical disk apparatus is operating.

The present invention is a program for causing a computer to perform the functions of all or some of the means (or apparatuses, elements, circuits, portions or the like) of the above-described optical recording apparatus of the present invention which program operates in cooperation with the computer.

Moreover, the present invention is a program for causing a computer to perform the operations of all or some of the steps

(or processes, operations, workings or the like) of the above-described optical recording method of the present invention which program operates in cooperation with the computer.

Moreover, the present invention is a medium carrying a program for causing a computer to perform all or some of the functions of all or some of the means of the above-described optical recording apparatus of the present invention, said medium being computer-readable and said program, being read, performing the functions in cooperation with the computer.

Moreover, the present invention is a medium carrying a program for causing a computer to perform all or some of the operations of all or some of the steps of the above-described optical recording method of the present invention, said medium being computer-readable and said program, being read, performing the operations in cooperation with the computer.

Some of the means (or apparatuses, elements, circuits, portions or the like) of the present invention and some of the steps (or processes, operations, workings or the like) of the present invention mean some of the plural means and some of the plural steps, respectively, or mean some functions of one means and some operations of one step, respectively.

Moreover, a usage of the program of the present invention may be such that the program is recorded on a computer-readable recording medium and operates in cooperation with a computer.

Moreover, a usage of the program of the present invention may be such that the program is transmitted over a transmission medium, is read by a computer and operates in cooperation with the computer.

Moreover, examples of the recording medium include ROMs, and examples of the transmission medium include a transmission medium such as the Internet, light, radio waves and sound waves.

Moreover, the above-mentioned computer of the present invention is not limited to pure hardware such as a CPU, but may include firmware, an OS, and peripherals.

As described above, the structure of the present invention may be realized either as software or as hardware.

While the output control of the present invention is performed at the time of writing onto the optical disk in the above-described embodiment, the present invention is not limited thereto. It may be performed at the time of reading from the optical disk.

While the information recording of the present invention is performed on an optical disk in the above-described embodiment, the present invention is not limited thereto. It may be performed on, for example, an optical memory card. To sum up, it is necessary for the information recording only to be performed on information recording media for performing information recording and reproduction by use of light energy.

The output control of the present invention may be

performed all the time while recording is performed or may be performed at regular time intervals. However, it is to be noted that control can more accurately be performed by the former manner.

It is necessary to set the value of the output  $P_0$  under the ideal condition by initial learning at the time of start of recording, because the value depends on the composition of the recording film of the optical disk and varies, for example, among the disk manufacturers. However, since a certain amount of aberrations are generated in actuality when initial learning is performed, the ideal condition where  $S=0$  is difficult to realize. Therefore, the following consideration is made:

When the aberration detection value and the set light source output at the time of initial learning are  $S_i$  and  $P_i$ , respectively, as is apparent from the description given above, [Expression 15]

$$P_i = P_0 / (1 - K \cdot S_i^2)$$

holds. Therefore, by erasing  $P_0$  from the expression 7 by use of the expression 15,

[Expression 16]

$$P = P_i (1 - K \cdot S_i^2) / (1 - K \cdot S^2)$$

is obtained. Although the expression 16 is nothing but the expression 17 when  $S_i=0$ , control can more accurately be performed by storing  $S_i$  and  $P_i$  obtained by initial learning as described above and calculating the light source output to be set while

the apparatus is operating.

The optical recording apparatus of the present invention may have initial learning means of initially learning the optimum light source output corresponding to the recording medium and initial learning result storage means of storing the result of the initial learning.

As described above, by adding the present invention to the conventional LPC (Laser Power Control), for example, since the light source output compensation amount can be obtained directly from the aberration detection signal, output compensation can be performed also for energy decreasing factors that cannot be dealt with by the conventional method, so that deterioration of recording signal quality can be suppressed.

As is apparent from the description given above, the present invention has an advantage that an optical recording apparatus, an optical recording method, a medium and an information aggregate capable of suppressing the deterioration of recording signal quality that cannot be prevented by the conventional method can be provided.